

4000 N

OPENNESS FACTOR 1%,5%

4000 N

SUNSHADOW

FABRIC

Technical specifications	Average Values		Standard
Openess Factor	1%	5%	Microscopic Method
Composition	Green PVC 73% Polyester 27%	Green PVC 73% Polyester 27%	ISO 1833-1:2006
Environment			<ul style="list-style-type: none"> · Oeko-tex standard 100 · GREENGUARD Children & Schools
Thickness	0.89mm (±5%)	0.73mm (±5%)	ISO 5084-1996
Weight	608g / m ² (±5%)	532g/m ² (±5%)	ISO 3081-1977
Fabric Count (sq.inch)	50ends X 33picks (±5%)	38ends X 38picks (±5%)	ISO 7211/2-1984
Tensile Strength (daN/5cm)	Warp 290, Weft 197 (±5%)	Warp 216, Weft 222 (±5%)	ISO 1421-1998
Tearing Strength (daN)	Warp 8.3, Weft 13.7 (±5%)	Warp 9.6, Weft 10.1 (±5%)	ISO 4674-1977
Colourfastness	7 - 8 Grade ISO Blue Scale		ISO 105 B02:1994
Fire resistance	M1		NF P 92-512 (EU)
	FR		NFPA 701 (USA)
	Type B		BS 5867 (U.K)
	B1, B2		DIN 4102 (GERMANY)
	AS/NZS		ISO 1530.3-1999 (AUSTRALIA)
	B1		GB / 5T455-1997(CHINA)
	KFI		ISO 5659 (KOREA)
Standard Width	2.0M / 2.5M / 3.0M		
Cutting	best result with crush cutting		
Welding	thermal, HF, ultrasonic, sewing		
Cleaning	remove dust from the fabric surface, then wipe gently with a humind soft sponge while using a mild detergent		





BREATHEASY



Using a very clever scientific process, our factory has removed odor causing components from their specially formulated non-toxic PVC compound. We call it Low Odor Emission Technology (LOE). As a result, the entire Sunshadow® Sunscreen range has earned GREENGUARD® endorsement for Indoor Air Quality. Unlike most other Blind Fabrics, Sunshadow® Sunscreen has minimal odor and therefore is not linked to complaints from consumers who develop headaches or feel unwell after inhaling strong odors from other Blind Fabrics. LOE Technology is ideal for residential environments, but particularly beneficial for commercial developments where odors from Blind Fabrics can linger and circulate through air-conditioning making it uncomfortable for office workers.

FUTUREFOCUSED



Koper has a strong environmental compass. A commitment already demonstrated by Sunshadow, the world's first non-toxic PVC compound which is safe for families and workers. By investing heavily in research and development, our factory will continue to create newer, better and safer methods for manufacturing products. It will deliver products that meet the needs of consumers' now, while ensuring quality, durability and contemporary styling. Through the ongoing development of Sunshadow® Sunscreen Blind Fabric, our factory is committed to achieving - The World's BEST Sun Protection for Windows.

QUALITY



Our factory has a strong social conscience and it is from this platform that outstanding quality processes have been developed. Every aspect of manufacturing from top to bottom is quality managed in a state-of-the-art facility that encompasses a formulation plant, laboratory, research and development and a weaving factory. To this end, Sunshadow® Sunscreen has been endorsed by the world's most respected independent testing organizations: Oeko-Tex® which tests for the presence of volatile organic compounds; GREENGAURD® which tests for indoor air quality; and Ecospecifier® which is committed to ecologically aware, 'green' building products. Further, Sunshadow® Sunscreen has outstanding Fire Retardant qualities which have achieved international flame and smoke regulation accreditation. Sunshadow® Sunscreen has also achieved anti-bacterial and anti-fungal certification. The Sunshadow® Sunscreen range of fashion colors is also sound, supported by comprehensive colorfastness testing. Using Blue Scale exposure to "Very Intense" light, testing has delivered a grading of 7 to 8 from a possible best score of 8. As the world becomes more aware of greenhouse gases, carbon footprints and the depletion of natural resources, consumers are making conscious decisions to reduce energy consumption. Sunshadow® Sunscreen by Koper achieves between 20% to 40% in energy savings due to reduced interior temperature in summer and less heat loss in winter, and all without sacrificing the view! Sunshadow® Sunscreen offers see-through qualities and natural light while maintaining day time privacy.

ENVIRONMENTALLY AWARE



Koper is aware of the need for environmental responsibility. Our factory is among the world's leading manufacturers to embrace the environment and human well-being by developing and implementing better and safer products. This commitment is evident in the world's first non-toxic PVC compound which has been developed to coat polyester to form a yarn that is stronger, lighter and less expensive to produce than traditional vinyl coated glass fiber fabrics. But perhaps of greatest importance, Sunshadow® Sunscreen has been officially declared safe when independently tested for Volatile Organic Compounds by Oeko-Tex® Standards 100. In the process of creating safe non-toxic PVC, our factory removed the odors that can reduce interior air quality when Blind Fabrics are installed in homes and workplaces, unlike most competitor's Sunscreen products that pollute interior spaces with strong odors. We call this process of LOE - Low Odor Emission Technology and it has earned GREENGUARD® Indoor Air Quality endorsement. Further, Sunshadow® Sunscreen has been endorsed by Ecospecifier®, an international organization dedicated to sustainable building products and ecologically aware building practices. Ecospecifier® has tested and concluded that Sunshadow® Sunscreen Blind Fabrics are 'green.'


COLOR & RANGE

1%




N001
White | White

4001




N002
White | Beige

4002




N003
White | Grey

4003




N902
Charcoal | Bronze

4902



N202
Beige | Almond Buff


4202



N401
Castlerock | Castlerock


4401

5%




N001
White | White

R21




N002
White | Beige

R22




N003
White | Grey

R24




N008
White | Almond Buff

R23



N282
Beige | Beige, Almond Buff

R28



N009
White | Sedona Sage

R25

THE MAIN THERMAL AND OPTICAL FACTORS

THERMAL FACTORS

Ts Solar transmittance

proportion of solar energy transmitted through the fabric. A low percentage means the fabric performs well at reducing solar energy.

Rs Solar reflectance

proportion of solar radiation reflected by the fabric. A high percentage means the fabric performs well at reflecting solar energy.

As Solar absorptance

proportion of solar radiation absorbed by the fabric. A low percentage means the fabric absorbs little solar energy. Solar radiation is always partially transmitted through, absorbed or reflected by the fabric. The sum of all 3 equals 100.
Ts + Rs + As = 100% of solar energy.

g_{tot} Total solar factor

solar energy which actually penetrates into a room through the blind and glazing. A low value means good thermal performance.

OPTICAL FACTORS

OF Openness Factor

relative area of the openings in the fabric (hole). It is considered as independent of the colour. For fabrics with the same weave, it should be measured using the darkest colour in the range.

Tv Visible light transmittance

total percentage of light radiated through the fabric over a wavelength of 380 to 780nm (nanometers), called the visible spectrum (total illumination).

Thermal and optical factors

Description Colours	OF 1%									OF 5%							
	Thermal factors							Optical factors		Thermal factors					Optical factors		
	Fabric			Fabric + glazing g - value				Tv	Tuv	Fabric			Fabric + glazing g - value			Tv	Tuv
	Ts	Rs	As	1/8" CL	1/4" C/L	1/4" HA	Ts			Rs	As	1/8" CL	1/4" C/L	1/4" HA			
N001 White White	15	67	18	0.32	0.33	0.31	Tr	11	16	67	17	0.28	0.29	0.28	11	4	
N002 White Beige	13	62	25	0.35	0.35	0.33	0	9	14	58	28	0.34	0.33	0.30	9	4	
N003 White Grey	7	51	42	0.42	0.41	0.36	Tr	4	10	45	45	0.41	0.40	0.33	8	5	
N008 White Almond Buff	11	52	37	0.42	0.41	0.35	6	3	14	55	31	0.41	0.40	0.35	9	4	
N009 White Sedona Sage	9	48	43	0.44	0.43	0.36	5	3	10	45	45	0.16	0.15	0.15	11	5	
N202 Beige Almond Buff	14	52	34	0.43	0.42	0.36	Tr	9	10	39	51	0.44	0.43	0.35	8	6	
N282 Beige Beige, Almond Buff	5	32	63	0.54	0.52	0.41	3	2	19	48	33	0.24	0.23	0.22	7	17	
N401 Castlerock Castlerock	5	33	62	0.54	0.52	0.41	4	1	8	23	69	0.54	0.51	0.39	8	6	
N902 Charcoal Bronze	0	6	94	0.71	0.67	0.50	0	0	6	5	89	0.64	0.60	0.44	6	6	

APPLICATION

Internal blinds



Roller Blinds



Roof light Blinds



Roman Shades



Decorative Panels



Velums



Skylight Blinds

Tensile structures



Frame-Mounted



Stretched Ceilings



Fixed or Mobile Partitions, Walls and Separations



Shaped Structures



Volume Structures

Flooring & Wallcovering



Wallcovering Partitions



Rolls Flooring



Tiles Flooring